

GXT Series

Extra Heavy Duty Fabricated Steel Castor

- Heavy Duty Fabricated Castor
- Load Capacities: 500kg - 2700kg
- Power Towable to 4km/h
- Unique integrated axle means superior rolling performance and durability
- Powder Coated and zinc galvanised

All available in the following types



Machine Cast Nylon

Wheel Dia. (mm)	Tread Width (mm)	Bearing Type	Top Plate (mm)	Bolt Holes (mm)	Suit Bolt (mm)	Off-set (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Wheel Brake	Fixed
80	48	Ball	100x85	80x60	8	40	120	800	GXT80ASFMCD	GXT80BSFMCD	GXT80ARFMCD
100	48	Ball	100x85	80x60	8	40	140	900	GXT100ASFMCD	GXT100BSFMCD	GXT100ARFMCD
125	70	Ball	175x140	148x111/132x99	14	77.5	170	1500	GXT125ASFMCD	GXT125BSFMCD	GXT125ARFMCD
150	70	Ball	175x140	148x111/132x99	14	80	200	2200	GXT150ASFMCD	GXT150BSFMCD	GXT150ARFMCD
200	70	Ball	175x140	148x111/132x99	14	75	260	2500	GXT200ASFMCD	GXT200BSFMCD	GXT200ARFMCD
250	68	Ball	175x140	148x111/132x99	14	75	310	2700	GXT250ASFMCD	GXT250BSFMCD	GXT250ARFMCD



Polyurethane Tyre / Aluminium Centre

Wheel Dia. (mm)	Tread Width (mm)	Bearing Type	Top Plate (mm)	Bolt Holes (mm)	Suit Bolt (mm)	Off-set (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Wheel Brake	Fixed
80	48	Ball	100x85	80x60	8	40	120	500	GXT80ASFHUD	GXT80BSFHUD	GXT80ARFHUD
100	48	Ball	100x85	80x60	8	40	140	600	GXT100ASFHUD	GXT100BSFHUD	GXT100ARFHUD
125	70	Ball	175x140	148x111/132x99	14	77.5	170	1100	GXT125ASFHUD	GXT125BSFHUD	GXT125ARFHUD
150	68	Ball	175x140	148x111/132x99	14	48	224	1500	GXT150ASFHUD	GXT150BSFHUD	GXT150ARFHUD
200	68	Ball	175x140	148x111/132x99	14	60	275	2000	GXT200ASFHUD	GXT200BSFHUD	GXT200ARFHUD
250	64	Ball	175x140	148x111/132x99	14	75	310	2300	GXT250ASFHUD	GXT250BSFHUD	GXT250ARFHUD



UGXT Series

Ultra Heavy Duty Fabricated Steel Castor

- Taper Roller Bearing in Swivel Head
- Load Capacities: 6000kg - 8000kg
- Power Towable to 4km/h
- Unique integrated axle means superior rolling performance and durability
- 4 Ball Bearing in Wheel
- Powder Coated and zinc galvanised

All available in the following types



Machine Cast Nylon

Wheel Dia. (mm)	Tread Width (mm)	Bearing Type	Top Plate (mm)	Bolt Holes (mm)	Suit Bolt (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Wheel Brake	Fixed
200	100	Ball	255x215	210x160	18	75	280	6000	UGXT200ASFMCD	UGXT200BSFMCD	UGXT200ARFMCD
250	100	Ball	255x215	210x160	18	80	330	7000	UGXT250ASFMCD	UGXT250BSFMCD	UGXT250ARFMCD
300	100	Ball	255x215	210x160	18	90	380	8000	UGXT300ASFMCD	UGXT300BSFMCD	UGXT300ARFMCD

